



# SCISSOR LIFTS ZS1012DC-Li

Comply with New Zealand latest Standard AS/NZ1418:10-2011

## HIGHLIGHTS

### High Performance

- ▶ Strong capacity of 350kg with high working efficiency
- ▶ Lightweight only 2930KG
- ▶ Lithium-ion batteries features long service life that the running time increases by 30%, and could apply to -20°C cold working conditions, with 60 months warranty provided
- ▶ Fast-charging technology

### Cost Effectiveness

- ▶ Sawing- out tray easy to service
- ▶ Modularized and unitized parts easy to maintenance

### Top Protection

- ▶ Preheating function built-in for cold weather
- ▶ Smart Battery Management System (BMS) guarantees safe power

## FEATURES

### Standard Features

- ▶ Working height: 11.8m
- ▶ Platform elevated height: 9.8m
- ▶ Climbing up 25% degree slope

## WARRANTY

### Long Term Post Purchasing Services

- ▶ Up to 5 years structural warranty
- ▶ 2 years whole machine warranty

For all purchase enquiries please email:  
[info@lw-equipment.com](mailto:info@lw-equipment.com)



**L&W EQUIPMENT**  
GROUP LIMITED

Phone: 0212737369

Email: [info@lw-equipment.com](mailto:info@lw-equipment.com)

Website: <https://www.lw-equipment.com/>

Address: 5A Spedding Road, Whenuapai, Auckland

# ZOOMLION

## SCISSOR LIFTS ZS1012DC-LI

Comply with New Zealand latest Standard AS/NZ1418.10-2011

Size	Imperial	Metric
Work Height	38ft 9in	11.80m
A-Platform Height-Elevated	32ft 2in	9.80m
B-Platform Height-Stowed	4ft 7in	1.39m
C-Platform Length	7ft 7in	2.30m
D-Platform Width	3ft 8in	1.12m
Platform Extension	3ft	0.91m
E-Overall Height (Rails Up)	8ft 4in	2.53m
Overall Height (Rails Down)	6ft 7in	2m
F-Overall Length	8ft 2in	2.49m
G-Overall Width	3ft 9in	1.15m
H Wheelbase	6ft 1in	1.85m
I-Ground Clearance (Stowed)	4.5in	0.11m
J-Ground Clearance (Raised)	0.75in	0.02m

Performance	Imperial	Metric
Platform Capacity	770lb	350kg
Capacity on Deck Extension	250lb	113kg
Max. Number of Workers	Indoor: 2 Outdoor: 1	
Drive Speed (Stowed)	2.5mph	4km/h
Drive Speed (Raised)	0.5mph	0.8km/h
Turning Radius (Inside)	4in	0.1m
Turning Radius (Outside)	7ft 3in	2.2m
Lifting Motor	24V/4.5KW	
Drive Motor	24V/2x0.75KW	
Up/Down Time	60s/35s	
Gradeability	25%(14°)	
Max. Working Slope (Lateral/Vertical)	1.5°/3°	
Control	Proportional Control	
Drive	Front Wheels	
Brake	Front Wheels	
Tire	Ø15in x5in	Ø381mm x127mm

Power	Weight
230Ah Li-ion	Gross 2930KG
24V/30A	

