

SCISSOR LIFTS ZS0607ACW-Li

Comply with New Zealand latest Standard AS/NZ1418.10-201

HIGHLIGHTS

High Performance

- ▶ Strong capacity of 230kg with high working efficiency
- ▶ Lightweight only 1620KG
- ▶ Lithium-ion batteries features long service life that the running time increases by 30%, and could apply to -20°C cold working conditions, with 60 months warranty provided
- ▶ AC system offers higher working efficiency.

Cost Effectiveness

- ▶ Swing- out tray easy to service
- ▶ Modularized and unitized parts easy to maintenance

Top Protection

- ▶ IP67 rated waterproof protection on AC wheel motors
- ▶ Battery Management System (BMS) + Machine control system provide dual protection

FEATURES

Standard Features

- ▶ Working height: 7.8m
- ▶ Platform elevated height: 5.8m
- ▶ Can climb up 25 degree slope

WARRANTY

Long Term Post Purchasing Services

- ▶ Up to 5 years structural warranty
- ▶ 2 years whole machine warranty

For all purchase enquiries please email:
info@lw-equipment.com



L&W EQUIPMENT
GROUP LIMITED

Phone: 0212737369

Email: info@lw-equipment.com

Website: <https://www.lw-equipment.com/>

Address: 5A Spedding Road, Whenuapai, Auckland

ZOOMLION

SCISSOR LIFTS ZS0607ACW-Li

Comply with New Zealand latest Standard AS/NZ1418.10-2011

Size	Imperial	Metric
Work Height	25ft 7in	7.8m
A-Platform Height-Elevated	19ft	5.8m
B-Platform Height-Stowed	3ft 5in	1.05m
C-Platform Length	5ft 5in	1.65m
D-Platform Width	2ft 5in	0.74m
Platform Extension	3ft	0.91m
E-Overall Height (Rails Up)	7ft 3in	2.20m
Overall Height (Rails Down)	5ft 10in	1.79m
F-Overall Length	6ft 1in	1.85m
G-Overall Width	2ft 8in	0.81m
H Wheelbase	4ft 6in	1.37m
I-Ground Clearance (Stowed)	2.4in	0.06m
J-Ground Clearance (Raised)	0.65in	0.016m

Performance	Imperial	Metric
Platform Capacity	510lb	230kg
Capacity on Deck Extension	250lb	113kg
Max. Number of Workers	Indoor: 2 Outdoor: 1	
Drive Speed (Stowed)	2.5mph	4km/h
Drive Speed (Raised)	0.5mph	0.8km/h
Turning Radius (Inside)	4in	0.1m
Turning Radius (Outside)	5ft3in	1.6m
Lifting Motor	24V/3.3KW	
Drive Motor	24V/0.65KW	
Up/Down Time	20s/24s	
Gradeability	25%(14°)	
Max. Working Slope (Lateral/Vertical)	1.5°/3°	
Control	Proportional Control	
Drive	Front Wheels	
Brake	Front Wheels	
Tire	Ø13in x4in	Ø323mm x100mm

Power

Battery	160Ah li-ion
Charger	24V/30A
Charger (option)	

Weight

	Imperial	Metric
Gross	3570lb	1620KG

